

06-27-00

A

Please type a plus sign (+) inside this box → ☒

PTO/SB/05 (4/98)
 Approved for use through 09/30/2000. OMB 0651-0032
 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. 991476
 First Inventor or Application Identifier Joshi
 Title SANITIZING DEVICE AND ASSOCIATED METHOD
 Express Mail Label No. EL 566160063 US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☐ * Fee Transmittal Form (e.g., PTO/SB/17)
 (Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages 25]
 (preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the invention
 - Brief Summary of the invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 4]
4. Oath or Declaration [Total Pages 2]
- a. ☒ Newly executed (original or copy)
 (unsigned)
- b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
 (for continuation/divisional with Box 16 completed)
- i. ☐ DELETION OF INVENTOR(S)
 Signed statement attached deleting
 inventor(s) named in the prior application,
 see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY
 FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT
 IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28).

ADDRESS TO: Assistant Commissioner for Patents
 Box Patent Application
 Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission
 (if applicable, all necessary)
- a. ☐ Computer Readable Copy
- b. ☐ Paper Copy (identical to computer copy)
- c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement of Power of Attorney
 (when there is an assignee) ☒
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
 (Should be specifically itemized)
13. ☐ * Small Entity Statement filed in prior application,
 Statement(s) Status still proper and desired
 (PTO/SB/09-12)
14. ☐ Certified Copy of Priority Document(s)
 (if foreign priority is claimed)
15. ☐ Other:

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No: _____ / _____

Prior application information: Examiner _____

Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

Name

PATENT TRADEMARK OFFICE

Address

City

State

Zip Code

Country

Telephone

Fax

Name (Print/Type)

Jody L. Factor

Registration No. (Attorney/Agent)

34157

Signature

Date

6/26/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

TITLE OF THE INVENTION**SANITIZING DEVICE AND ASSOCIATED METHOD****BACKGROUND OF THE INVENTION**

5 1. Field of the Invention

The present invention relates in general to a sanitizing device having an electrochemical, chemical, and/or corona cell, and more particularly, to a sanitizing device having an electrochemical, chemical, and/or corona cell as a component to sanitize, disinfect, sanitize, and/or otherwise beneficially effect surfaces, liquids, gasses, and/or associated surrounding environments.

10 2. Background Art

Sanitizing devices have been known in the art for several years and are the subject of many United States Patents including: U.S. Patent No. 5,874,050; U.S. Patent No. 5,441,710; U.S. Patent No. 3,691,346; U.S. Patent No. 3,654,432; and U.S. Patent No. 15 5,928,481.

U.S. Patent No. 5,874,050 discloses a room air sterilization device having an elongated member with a plurality of narrow, substantially parallel passages extending from a first end to a second end. Heating wire, preferably fabricated from a nickel chromium resistive material, is positioned within the passages. Upon application of a power source, including AC/DC current, the heating wire radiates heat within the passages, thereby raising the air to a sufficient temperature to become sterilized and rise from the passage via convection current.

U.S. Patent No. 5,441,710 discloses an air flow sterilizer for destroying microorganisms by heating an air flow to a sufficient temperature to weaken cellular

walls of the microorganisms. Turbulence is introduced into the air flow so that the weakened microorganisms are destroyed upon hitting a surface of the turbulent chamber.

U.S. Patent No. 3,654,432 discloses an electrically heated catalytic air purifier having a heating unit for treating air borne particles. The heating unit includes a surface coating of silicon carbide which functions at an operating temperature between 250 and 350 degrees centigrade.

U.S. Patent No. 5,928,481 discloses an apparatus for sterilizing water by the process of heavy metal sterilization using silver.

SUMMARY OF THE INVENTION

The present invention is directed to a sanitizing device comprising: (a) a sanitizing component for sanitizing a surface, liquid, gas, and/or associated surrounding environment, wherein the sanitizing component includes an electrochemical, chemical, and/or corona cell; and (b) a housing for retaining the sanitizing component.

In a preferred embodiment of the invention, the sanitizing component comprises a porous matrix substantially impregnated with a material selected from the group consisting essentially of peroxides, superoxides, fluorates, chlorates, bromates, iodates, permanganates, and mixtures thereof. In this embodiment the porous matrix may comprise one or more materials selected from the group consisting essentially of plastics, carbonaceous materials, ceramics, metals, and mixtures thereof.

In another preferred embodiment of the invention the sanitizing device further comprises power means for powering an electrochemical and/or corona cell, wherein the power means consists of AC current and/or DC current. In this embodiment the sanitizing component preferably comprises the electrochemical and/or corona cell.

If a corona cell is associated with the sanitizing device of the present invention, it is preferred that such a corona cell comprise a dielectric material and two electrodes.

If an electrochemical cell is associated with the sanitizing device of the present invention, it is preferred that such an electrochemical cell include an anodic component, a cathodic component, and an electrolyte component. The electrolyte component may comprise a solid phase material, and may also serve as a partial or full component of the device, such as, for example, a housing, porous matrix, or particulate filtering component.

Preferably both the anodic component and the cathodic component comprise the same or different materials selected from the group consisting essentially of metals such as, titanium, nickel, steel, copper, silver, platinum, palladium, zinc, aluminum, and mixtures and alloys thereof, and conductive ceramics such as, perovskites, carbides and nitrides of metals.

In yet another preferred embodiment of the invention, the electrolyte component comprises a material selected from the group consisting essentially of a halide containing material, an oxide containing material, an ion exchange membrane, an alkali ion conducting material, a silver or copper ion conducting material, and an ion conducting ceramic material and mixtures, compounds, and alloys thereof. In this embodiment the halide containing material may include halides of metals, their mixtures and compounds as well as their composites with plastic and ceramic materials. Oxide containing materials may include composites of metal oxides and ion conducting materials (e.g. AgI-Al₂O₃ composites) as well as beta-aluminas's (M_xO-11Al₂O₃) or Nasicon materials.

In accordance with the present invention, an ion exchange membrane may comprise Nafion, Nasicon, and/or beta-alumina materials in which any monovalent or divalent ion can be substituted such as, for example, Ag, Cu, Li, Rb, Cs, Na, H, Mg, Etc.

In accordance with the present invention, silver and copper ion conducting materials may include inorganic and/or organic compounds of silver and/or copper (e.g. halides, chalcogenides, phosphates, tungstates, zirconates, aluminates, and titanates of silver and/or copper), which have ionic conductivity greater than approximately 10⁻¹⁰ (ohm cm)⁻¹ at ambient temperatures.

In accordance with the present invention alkali ion conducting materials may include lithium, sodium, rubidium, cesium ion conducting materials with ionic conductivity greater than approximately $10^{-10}(\text{ohm cm})^{-1}$ at ambient temperatures.

5 In yet another preferred embodiment of the present invention, the dielectric material of an associated corona cell may comprise a material selected from the group consisting of an oxide containing ceramic material and/or plastic material having a dielectric constant less than 100 and an electronic conductivity less than $10^{-7}(\text{ohm cm})^{-1}$.

10 In accordance with the present invention, an electrode associated with a corona cell may comprise materials selected from the group consisting essentially of metals such as, for example, titanium, nickel, steel, copper, silver, platinum, tungsten, palladium, aluminum, and mixtures and alloys thereof, as well as conductive ceramics such as, perovskites, carbides and nitrides of metals and mixtures thereof.

15 In a preferred embodiment of the invention, a particulate filtering component may also be associated with the housing which is capable of substantially trapping particulates thereon, such as an activated carbonaceous filter component.

Preferably the sanitizing device of the present invention is also associated with forced air means including a fan, a blower, etc.

20 The present invention is also directed to a multi-layer composite sanitizing device comprising: (a) a sanitizing component associated with a housing for sanitizing a surface, liquid, gas, and/or associated surrounding environment, wherein the sanitizing component includes an electrochemical, chemical, and/or corona cell; (b) a particulate filtering component capable of substantially trapping particulates thereon; and (c) a housing for

retaining the sanitizing component and the particulate filtering component.

The present invention is further directed to a process for sanitizing a surface comprising the steps of: (a) providing a sanitizing component such as an electrochemical, chemical, and/or corona cell retained within a housing; (b) contacting the sanitizing component of the device with a surface; and (c) substantially sanitizing the surface.

The present invention is further directed to a process for sanitizing a liquid, gas and/or other matter, comprising the steps of: (a) providing a sanitizing component such as an electrochemical, chemical, and/or corona cell retained within a housing; (b) passing liquid, gas, and/or other matter over the sanitizing component; (c) contacting the sanitizing component with the liquid, gas, and/or other matter; and (d) substantially sanitizing the liquid, gas, and/or other matter.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will now be described with reference to the drawings wherein:

Fig. 1 of the drawings is a schematic representation of a sanitizing device in accordance with the present invention;

5 Fig. 2 of the drawings is a fragmented side view of a sanitizing device in accordance with the present invention showing an electrochemical sanitizing component;

Fig. 3 of the drawings is a side view of a sanitizing device accordance with the present invention showing an electrochemical sanitizing component associated with a particulate filtering component;

10 Fig. 4 of the drawings is a side view of a sanitizing device in accordance with the present invention showing an electrochemical sanitizing component associated with both a particulate filtering component as well as with fragrance emitting means;

Fig. 5 of the drawings is a side view of a sanitizing device in accordance with the present invention associated with forced air means;

15 Fig. 6 of the drawings is a schematic representation of a sanitizing device in accordance with the present invention configured as a water purifier;

Fig. 7 of the drawings is a schematic representation of a sanitizing device in accordance with the present invention configured as a surface disinfectant device; and

20 Fig. 8 of the drawings is a schematic representation of a sanitizing device in accordance with the present invention configured as a surrounding area sanitizing device.

DETAILED DESCRIPTION OF THE INVENTION

While this invention is susceptible of embodiment in many different forms, there is shown in the drawings and described herein in detail several specific embodiments with the understanding that the present disclosure is to be considered as an exemplification of the principles of the invention and is not intended to limit the invention to the embodiments illustrated.

It will be understood that like or analogous elements and/or components, referred to herein, are identified throughout the drawings by like reference characters. In addition, although the term "sanitizing" will be used throughout the disclosure, it should be understood that the device is also capable of "purifying" as well.

Referring now to the drawings and to Fig. 1 in particular, sanitizing device 10 is shown in a first embodiment as generally comprising housing 12 and sanitizing component 14 for sanitizing contaminants, such as microorganisms, germs, bacteria, viruses, undesirable chemicals and/or compounds, etc. Housing 12 may be fabricated from any one of a number of materials including natural and synthetic resins, plastics, metals, woods, etc. While sanitizing device 10 has been shown as being substantially rectangular, numerous other geometric configurations are likewise contemplated for use including generally circular, generally elliptical, generally square, generally triangular, generally polygonal, and generally arbitrary – just to name a few.

For purposes of the present invention, sanitizing component 14 includes an electrochemical, chemical, and/or corona cell or purifier. The chemical purifier preferably comprises a porous matrix substantially impregnated with one or more of the following

materials, namely: peroxides; superoxides; fluorates; chlorates; bromates; iodates; and permanganates. While it is desirous for the above-identified materials to be relatively pure, the presence of nominal amounts of other materials does not appear to be detrimental to the present invention – so long as the concentration of the sanitizing material remains high enough to perform its intended function of killing a substantial majority of the above-identified contaminants. The porous matrix of sanitizing component 14 is preferably fabricated from carbonaceous materials, plastics, ceramics, metals, and mixtures thereof.

When an electrochemical and/or corona cell or purifier is incorporated into sanitizing device 10, it may be operated by AC current and/or DC current. However, numerous other power means that would be known to those having ordinary skill in the art are likewise contemplated for use. As is shown in Fig. 2, sanitizing component 14 may include an electrochemical cell 15 comprising anodic component 16, cathodic component 18, and electrolyte component 20.

Anodic component 16 and cathodic component 18 may be fabricated from the same or different materials, including metals, conductive ceramics (including a particulate filtering component), and mixtures thereof. Preferred metals include transition metals such as titanium, nickel, copper, silver, platinum, palladium, zinc, as well as aluminum, steel, and mixtures and alloys thereof, and preferred conductive ceramics include perovskites, carbides, nitrides of metals, and mixtures thereof.

While preferred anodic and cathodic component materials have been disclosed, for illustrative purposes only, it will be understood that numerous other conventional

anodic and cathodic materials are likewise contemplated for use.

Electrolyte component 20 may be fabricated from several materials including, for example, a halide containing material, an oxide containing material, an ion exchange membrane, an alkali ion conducting material, a silver or copper ion conducting material, and an ion conducting ceramic material and mixtures, compounds, and alloys thereof.

Preferred halide containing materials include halides of metals, their mixtures and compounds as well as their composites with plastic and ceramic materials. For example, the halide containing material may include one or more of the following materials, PbI_2 , PbF_2 , LaF_3 , AgRbI_5 , $\text{AgI-Al}_2\text{O}_3$, $\text{CuI-Al}_2\text{O}_3$, and mixtures thereof

In accordance with the present invention, oxide containing materials may include composites of metal oxides and ion conducting materials (e.g. $\text{AgI-Al}_2\text{O}_3$ composites) as well as beta-aluminas ($\text{M}_x\text{O} \cdot 11\text{Al}_2\text{O}_3$) or Nasicon materials.

Preferably, an ion exchange membrane may comprise Nafion, Nasicon, and/or beta-alumina materials in which any monovalent or divalent ion can be substituted such as, for example, Ag, Cu, Li, Rb, Cs, Na, H, Mg, Etc.

Suitable silver and copper ion conducting materials may include inorganic and/or organic compounds of silver and/or copper (e.g. halides, chalcogenides, phosphates, tungstates, zirconates, aluminates, and titanates of silver and/or copper), which have ionic conductivity greater than approximately $10^{-10} (\text{ohm cm})^{-1}$ at ambient temperatures.

In accordance with the present invention, alkali ion conducting materials may include lithium, sodium, rubidium, cesium ion conducting materials with ionic conductivity greater than approximately $10^{-10} (\text{ohm cm})^{-1}$ at ambient temperatures.

While several specific electrolyte components have been disclosed, for illustrative purposes only, it will be understood that other electrolyte components are suitable for use in accordance with the present invention – so long as the particular material(s) substantially sanitize associated contaminants contained therein.

5 If a corona cell is associated with the present invention, such cell may comprise electrode materials selected from the group consisting essentially of metals such as, for example, titanium, nickel, steel, copper, silver, platinum, tungsten, palladium, aluminum, and mixtures and alloys thereof, as well as conductive ceramics such as, perovskites, carbides and nitrides of metals and mixtures thereof. Further, if a corona cell is
10 associated with the present invention, then such a cell may comprise dielectric materials selected from the group consisting of metal oxides such as titanium, aluminum and silicon oxides.

As is shown in Fig. 3, particulate filtering component 22 may also be associated with the sanitizing device 10. Particulate filtering component 22 is capable of
15 substantially trapping particulates thereon, and is preferably fabricated from activated carbonaceous material(s). Particulate filtering component 22 is also capable of deodorizing an associated unclean medium (e.g. liquids including water, gasses including air, and mixtures of both). In accordance with the present invention, particulate filtering component 22 traps relatively larger components of an unclean medium, such as air borne
20 dust, hair, dirt, etc. In this embodiment particulate filtering component 22 may be positioned in front or behind sanitizing component 14, although it is preferred that sanitizing component 14 is positioned behind particulate filter component 22 so that

incoming medium will contact the particulate filtering component first.

As is shown in Fig. 4, sanitizing device 10 may also include fragrance emitting means 24, such as a conventional electrochemical fragrance dispenser or a porous matrix material (as disclosed above) impregnated with a desired fragrant material. In this embodiment, the precise order of each component is not critical, however, it is preferred that particulate filtering component 22 is positioned before sanitizing component 14, and that fragrance emitting mean is positioned last so that incoming medium will be filtered for particulates and disinfected prior to being associate with a fragrant material.

As is shown schematically in Fig. 5, sanitizing device 10 may also be associated with forced air means 26, such as a fan, a blower, etc. In this embodiment, unclean medium (in this case air) is directed to the device so that the sanitizing process can be expedited.

While specific multi-layer composite device configurations have been disclosed, for illustrative purposes only, it will be understood that numerous multi-layer composite configurations are contemplated for use including, but by no means limited to, the following: AB; BA; BC; CB; ABC; BCA; CBA; AAB; BBC; ABAC, ABBC, AABBC; and ABCABC:

Wherein A = a particulate filtering component;

Wherein B = a sanitizing component; and

Wherein C = fragrance emitting means.

In operation, when a sanitizing component retained within a housing is only provided, unclean medium passes through sanitizing device 10, whereby the unclean

medium having contaminants contacts sanitizing component 14. Upon contact with the sanitizing component, the contaminants contained within the unclean medium are beneficially altered or killed by "active materials" either impregnated into the porous matrix (in the case of a chemical purifier) or contained within an electrode or the electrolyte (in the case of an electrochemical purifier).

Alternatively, if particulate filtering component 22 is also associated with sanitizing device 10, the unclean medium preferably first passes through particulate filtering component 22, whereupon particulates are substantially trapped and do not continue into the sanitizing component. Adding such a component is desirous for conditions where relatively larger particulates may be found such as dirt, dust, hair, etc.

In addition, when fragrance emitting means 24 are associated with sanitizing device 10, the unclean medium is preferably impregnated with a desirable fragrance just prior to exiting the filter. As such, although not necessary, it is preferable to have fragrance emitting means positioned as the last sanitizing device component.

It will be understood that sanitizing device 10 may be incorporated into any one of a number of sanitizing applications. For example, sanitizing device 10 may be configured for use in association with AC and/or DC powered portable air sanitizing devices. Alternatively, sanitizing device 10 may be configured to replace or supplement conventional filters in forced air heating/cooling systems including those in homes, commercial building, vehicles, airplanes, boats, etc. In such an application, sanitizing device 10 may be positioned in several places including, immediately prior or subsequent to any forced air means, immediately prior to a vent or register – just to name a few.

As is shown in Fig. 6, sanitizing device 10 may be operatively configured as a portable water purifier. In this embodiment sanitizing device 10 generally comprises housing 12, sanitizing component 14, filtering component 22, and reservoir member 28. For purposes of the present disclosure sanitizing component 14 may comprise an electrochemical and/or corona cell which is powered by AC current and/or DC current 25. Preferably the sanitizing component includes an electrochemical and/or corona cell that is generally porous so that water or other media can transport through such a cell.

In operation, a user pours a medium, such as water, on the top of filtering component 22, whereby particulates are isolated on top of the filtering component. Next the medium is gravity fed into reservoir member 28, whereupon the medium contacts sanitizing component 14. In accordance with above-identified embodiments, sanitizing member 14 purifies the medium upon contact. Once purified the medium is retained within the bottom of housing 12 for subsequent use.

As is shown in Fig. 7, sanitizing device 10 may be operatively configured as a surface disinfectant device. In this embodiment sanitizing device 10 generally comprises housing 12 and sanitizing component 14. For purposes of the present disclosure sanitizing component 14 may comprise an electrochemical and/or corona cell which is powered by AC current and/or DC current 25. In operation, a user places sanitizing device 10 onto surface 30, whereupon application of an applied potential to sanitizing component 14, surface 30 is purified.

As is shown in Fig. 8, sanitizing device 10 may be operatively configured as a surrounding area sanitizing device. In this embodiment sanitizing device 10 generally

comprises housing 12, sanitizing component 14, and forced air means 26. For purposes of the present disclosure sanitizing component 14 may comprise an electrochemical, chemical, and/or corona cell, which may be powered by AC current and/or DC current 25 if necessary. In operation, a user places sanitizing device 10 in a surrounding environment, such as a room. Once positioned, sanitizing component 14 and forced air means 26 are activated by application of an applied potential. Forced air means 26 inputs the surrounding environment within housing 12, whereby the surrounding environment contacts sanitizing component 14 which purifies the surrounding environment. Once purified, the surrounding environment is expelled out of housing 12 through a porous portion of sanitizing component or an aperture associated therewith.

It will be understood that the term "sanitize" is herein defined as the function of sanitizing, disinfecting, and/or otherwise beneficially effecting surfaces, liquids, gasses, and/or surrounding environments.

The foregoing description merely explains and illustrates the invention and the invention is not limited thereto except insofar as the appended claims are so limited, as those skilled in the art who have the disclosure before them will be able to make modifications without departing the scope of the invention.

WHAT IS CLAIMED IS:

1. A sanitizing device, comprising:

- a sanitizing component for sanitizing a surface, liquid, gas, and/or associated surrounding environment, wherein the sanitizing component includes an electrochemical, chemical and/or corona cell; and

- a housing for retaining the sanitizing component.

2. The sanitizing device according to claim 1, wherein the sanitizing component comprises a porous matrix substantially impregnated with a material selected from the group consisting essentially of peroxides, superoxides, fluorates, chlorates, bromates, iodates, permanganates, and mixtures thereof.

3. The sanitizing device according to claim 2, wherein the porous matrix comprises at least one material selected from the group consisting essentially of plastics, carbonaceous materials, ceramics, metals, and mixtures thereof.

4. The sanitizing device according to claim 1, further comprising power means for powering an electrochemical and/or corona cell, wherein the power means consists of AC current and/or DC current.

5. The sanitizing device according to claim 4, wherein the sanitizing component comprises an electrochemical and/or corona cell.

6. The sanitizing device according to claim 5, wherein the electrochemical cell comprises an anodic component, a cathodic component, and an electrolyte component.

7. The sanitizing device according to claim 6, wherein the anodic component comprises a material selected from the group consisting essentially of metals, carbonaceous materials, and mixtures thereof.

8. The sanitizing device according to claim 7, wherein the anodic component comprises a metal selected from the group consisting essentially of titanium, nickel, steel, copper, silver, platinum, palladium, zinc, aluminum, and mixtures and alloys thereof.

9. The sanitizing device according to claim 7, wherein the anodic component comprises a transition metal.

10. The sanitizing device according to claim 6, wherein the cathodic component comprises a material selected from the group consisting essentially of metals, carbonaceous materials, and mixtures thereof.

11. The sanitizing device according to claim 10, wherein the cathodic component comprises a metal selected from the group consisting essentially of titanium, nickel, steel, copper, silver, platinum, palladium, zinc, aluminum, and mixtures and alloys thereof.

12. The sanitizing device according to claim 10, wherein the cathodic component comprises a transition metal.

13. The sanitizing device according to claim 6, wherein the electrolyte component
5 comprise a solid phase electrolyte.

14. The sanitizing device according to claim 13, wherein the solid phase electrolyte comprises a porous matrix.

15. The sanitizing device according to claim 5 wherein its electrochemical and/or
10 corona cell allows fluid to pass through their structure.

16. The sanitizing device according to claim 6, wherein the electrolyte component
comprises a material selected from the group consisting essentially of a halide containing
material, an oxide containing material, an ion exchange membrane, an alkali ion
conducting material, a silver or copper ion conducting material, and an ion conducting
15 ceramic material, and mixtures thereof.

17. The sanitizing device according to claim 1, further comprising a particulate
20 filtering component associated with the housing, wherein the particulate filtering
component is capable of substantially trapping particulates thereon.

18. The sanitizing device according to claim 17, wherein the particulate filtering component comprises an activated carbonaceous filter component.

19. The sanitizing device according to claim 1, further comprising fragrance emitting means associated with the housing.

20. The sanitizing device according to claim 19, wherein the fragrance emitting means comprises an electrochemical fragrance dispenser or a porous matrix material impregnated with a fragrance.

21. The sanitizing device according to claim 1, further associated with forced air means.

22. The sanitizing device according to claim 21, wherein the forced air means comprises a fan or a blower.

23. A multi-layer composite sanitizing device, comprising:

- a particulate filtering component capable of substantially trapping particulates thereon;

- a sanitizing component for sanitizing a surface, liquid, gas, and/or associated surrounding environment, wherein the sanitizing component includes an electrochemical, chemical and/or corona cell; and

- a housing for retaining the particulate filtering component and the sanitizing component.

24. The multi-layer composite sanitizing device according to claim 23, wherein the sanitizing component comprises a porous matrix substantially impregnated with a material selected from the group consisting essentially of peroxides, superoxides, fluorates, chlorates, bromates, iodates, permanganates, and mixtures thereof.

25. The multi-layer composite sanitizing device according to claim 24, wherein the porous matrix comprises at least one material selected from the group consisting essentially of plastics, carbonaceous materials, ceramics, metals, and mixtures thereof.

26. The multi-layer composite sanitizing device according to claim 23, further comprising power means for powering an electrochemical and/or corona cell, wherein the power means consists of AC current and/or DC current.

27. The multi-layer composite sanitizing device according to claim 26, wherein the sanitizing component comprises an electrochemical and/or corona cell.

28. The multi-layer composite sanitizing device according to claim 27, wherein the electrochemical cell comprises an anodic component, a cathodic component, and an electrolyte component.

29. The multi-layer composite sanitizing device according to claim 28, wherein the anodic component comprises a material selected from the group consisting essentially of metals, carbonaceous materials, and mixtures thereof.

5

30. The multi-layer composite sanitizing device according to claim 29, wherein the anodic component comprises a metal selected from the group consisting essentially of titanium, nickel, steel, copper, silver, platinum, palladium, zinc, aluminum, and mixtures and alloys thereof.

10

31. The multi-layer composite sanitizing device according to claim 29, wherein the anodic component comprises a transition metal.

15

32. The multi-layer composite sanitizing device according to claim 28, wherein the cathodic component comprises a material selected from the group consisting essentially of metals, carbonaceous materials, and mixtures thereof.

20

33. The multi-layer composite sanitizing device according to claim 32, wherein the cathodic component comprises a metal selected from the group consisting essentially of titanium, nickel, steel, copper, silver, platinum, palladium, zinc, aluminum, and mixtures and alloys thereof.

34. The multi-layer composite sanitizing device according to claim 32, wherein the

cathodic component comprises a transition metal.

35. The multi-layer composite sanitizing device according to claim 28, wherein the electrolyte component comprise a solid phase electrolyte.

5

36. The multi-layer composite sanitizing device according to claim 35, wherein the solid phase electrolyte comprises at least one of at least a portion of the housing, a porous matrix, and a particulate filtering component.

37. The multi-layer composite sanitizing device according to claim 28, wherein the electrolyte component comprises a material selected from the group consisting essentially of a halide containing material, an oxide containing material, an ion exchange membrane, an alkali ion conducting material, a silver or copper ion conducting material, an ion conducting ceramic material, and mixtures thereof.

38. The multi-layer composite sanitizing device according to claim 23, further comprising a particulate filtering component associated with the housing, wherein the particulate filtering component is capable of substantially trapping particulates thereon.

39. The multi-layer composite sanitizing device according to claim 38, wherein the particulate filtering component comprises an activated carbonaceous filter component.

40. The multi-layer composite sanitizing device according to claim 23, further

comprising fragrance emitting means associated with the housing.

41. The multi-layer composite sanitizing device according to claim 40, wherein the fragrance emitting means comprises an electrochemical fragrance dispenser or a porous matrix material impregnated with a fragrance.

42. The multi-layer composite sanitizing device according to claim 23, further associated with forced air means.

43. The multi-layer composite sanitizing device according to claim 42, wherein the forced air means comprises a fan or a blower.

44. A process for sanitizing a liquid, gas or other matter, comprising the steps of:

- providing a sanitizing component such as an electrochemical, chemical, and/or corona cell retained within a housing;
- passing liquid, gas, or other matter over the sanitizing component;
- contacting the sanitizing component with the liquid, gas, or other matter, and
- substantially sanitizing the liquid, gas, or other matter.

45. The process according to claim 44, wherein the liquid, gas or other matter is on a surface.

ABSTRACT

A sanitizing device comprising: a sanitizing component for sanitizing a surface, liquid, gas, and/or associated surrounding environment, wherein the sanitizing component includes an electrochemical, chemical, and/or corona cell; and a housing for retaining the sanitizing component. A particulate filtering component capable of substantially trapping particulates thereon and fragrance emitting means are also provided.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

Please type a plus sign (+) inside this box:

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	991476
	First Named Inventor	Joshi
	COMPLETE IF KNOWN	
	Application Number	/
	Filing Date	June 26, 2000
	Group Art Unit	
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)
Examiner Name		

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

SANITIZING DEVICE AND ASSOCIATED METHOD

the specification of which *(Title of the Invention)*

☒ is attached hereto
OR
☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number
Jody L. Factor	34157	William L. King	P46830
Jovan N. Jovanovic	40039		
Kalim S. Fuzail	45805		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number OR ☐ Correspondence address below

Name	Jody L. Factor				
Address	FACTOR & PARTNERS, LLC				
Address	100 W. Monroe St., Suite 300				
City	Chicago	State	IL	ZIP	60603
Country	US	Telephone	312-578-0400	Fax	312-578-8220

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:		<input type="checkbox"/> A petition has been filed for this unsigned inventor			
Given Name (first and middle (if any))		Family Name or Surname			
Ashok V.		Joshi			
Inventor's Signature				Date	
Residence: City	Salt Lake City	State	UT	Country	US
Post Office Address	4552 S. Thousand Oaks Drive				
Post Office Address					
City	Salt Lake City	State	UT	ZIP	84124
		Country	US		

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto